



**UNIVERSITI PUTRA MALAYSIA**

**ACTIVE MICROSTRIP ANTENNA DESIGN  
FOR GLOBAL POSITIONING  
SYSTEM APPLICATION**

**SHARLENE THIAGARAJAH**

**FK 2000 18**

**ACTIVE MICROSTRIP ANTENNA DESIGN FOR GLOBAL POSITIONING  
SYSTEM APPLICATION**

**By**

**SHARLENE THIAGARAJAH**

**Thesis Submitted in Fulfilment of the Requirements for the  
Degree of Master of Science in the Faculty of Engineering  
Universiti Putra Malaysia**

**March 2000**



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirements for the degree of Master of Science.

## **ACTIVE MICROSTRIP ANTENNA DESIGN FOR GLOBAL POSITIONING SYSTEM APPLICATION**

By

**SHARLENE THIAGARAJAH**

**March 2000**

**Chairman :** Associate Professor Borhanuddin Mohd. Ali, Ph.D.

**Faculty :** Engineering

A circularly polarized microstrip antenna (MSA) was investigated for a commercial land-based Global Positioning System (GPS) application. Critical GPS antenna requirements are its gain, polarization and radiation characteristics. Advancements in electronic miniaturization techniques have made GPS receivers smaller and less bulky, paving the way for smaller antenna structures to improve aesthetic appearance. The crossed-drooping dipole, conventional and printed quadrifilar helix (QHA), archimedean spiral, conical spiral, printed cylindrical slot and the microstrip antenna were investigated for their circular polarization potential and broad beamwidth. Performance comparison analysis indicated the microstrip antenna as a suitable choice mainly for its simple design structure and attractive physical properties.

Two patch geometry, the circular and square patch antennas were fabricated and analyzed to investigate the MSA's design and fabrication sensitivity to geometry. Performance degradation due to fabrication tolerances is an important issue in

manufacturing. Experimental results showed good impedance matching and similar patch performance for both patches. The effect of patch size was also investigated using two different substrates. The only limitation of the MSA for GPS application was its low gain characteristic. However this was easily overcome by integrating an active circuit with the patch. A 16dB increase in gain was obtained without affecting its other performance parameters or low profile structure. GPS satellite acquisition measurements showed that the proposed active antenna could track satellites even at low elevation angles.

To further improve the axial ratio performance of the patch antenna, the effects of limited groundplane at GPS frequency L1 were investigated. Best axial ratio was obtained when groundplane surrounding radiating patch was kept as small as possible. Radiation pattern became omnidirectional but with lower gain characteristics. Attaching parasitic to patch periphery improved axial ratio but reduced gain further. The proposed omnidirectional antenna could find good use for GPS marine applications.

In conclusion the proposed active MSA is seen as a good candidate for commercial GPS applications. Its simple patch design is easy to fabricate and duplicate for mass production.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk Ijazah Master Sains.

## **ANTENA AKTIF MIKROJALUR UNTUK APLIKASI SISTEM KEDUDUKAN GLOBAL**

Oleh

**SHARLENE THIAGARAJAH**

**Mac 2000**

**Pengerusi :** **Profesor Madya Borhanuddin Mohd. Ali, Ph.D.**

**Fakulti :** **Kejuruteraan**

Penggunaan antena mikrojalur yang mempunyai medan pengutuban membulat telah dikaji kesesuaian untuk dikomersilkan untuk Sistem Kedudukan Global (GPS). Ciri-ciri antena sistem GPS yang penting adalah gandaan, pengutuban dan pola sinarannya. Kemajuan teknologi di sektor elektronik kini membolehkan saiz alat penerima GPS diperkecilkan lagi. Ini telah meningkatkan lagi kemahuan orang ramai untuk sistem antena yang lebih kecil dan tipis untuk mengurangkan lagi saiz keseluruhan alat penerima GPS. Antena dwikutub berjuntai, 'quadrifilar' heliks dalam bentuk asalnya dan tercetak, pilin 'archimedeian', pilin berbentuk kon, antena tercetak selinder berjalur dan antena mikrojalur telah dipilih untuk dikajiselidik umumnya kerana mempunyai ciri pengutuban membulat dan berkeupayaan menghasilkan pola sinaran yang lebar. Perbandingan prestasi kesemua struktur antena tersebut telah menunjukkan bahawa antena mikrojalur adalah yang paling sesuai untuk sistem GPS kerana rekabentuknya yang mudah dan ciri fizikalnya yang menarik.

Dua antena mikrojalur, satu berbentuk bulat dan yang satu lagi berbentuk segiempat telah dihasilkan untuk mengkaji samada prestasi antena mikrojalur akan berubah mengikut bentuk geometrinya. Toleransi dalam proses fabrikasi adalah isu penting dalam proses pengilangan komersil. Hasil ujikaji menunjukkan bahawa tiada perbezaan prestasi diantara kedua-dua geometri antena yang dihasilkan. Analisis perbandingan prestasi antena mikrojalur apabila saiznya berubah juga telah dikajiselidik menggunakan dua bahan mikrojalur yang berbeza. Satu-satunya kelemahan antena mikrojalur adalah gandaannya yang rendah. Walaubagaimanapun, kelemahan ini telah diatasi dengan menggunakan litar aktif. Gandaan sebanyak 16dB telah dapat dihasilkan tanpa mengganggu prestasi antena tersebut ataupun ciri fizikalnya yang tipis. Antena yang dicadangkan ini juga berjaya menerima isyarat satelit walaupun hampir di kaki langit.

Untuk mempertingkatkan lagi sifat pengutuban membulat antena tersebut, saiz permukaan buminya telah dikurangkan. Pada frekuensi GPS L1, didapati bahawa ciri pengutuban membulat bertambah baik apabila saiz permukaan bumi yang mengelilingi antenna tersebut diperkecilkan sebanyak mungkin. Pola sinaran menjadi bulat tetapi gandaannya berkurangan. Memasang parasitik mengelilingi antena tersebut telah dapat meningkatkan lagi ciri pengutuban membulatnya, tetapi ciri gandaanya menjadi rendah. Antena yang baru dicadangkan ini mungkin sesuai untuk aplikasi GPS semasa di laut.

Pada kesimpulannya, didapati bahawa antena aktif mikrojalur yang dicadangkan dalam tesis ini adalah calon yang sesuai untuk dikomersilkan untuk sistem GPS. Rekabentuknya mudah difabrikasi dan dihasilkan dalam kuantiti yang besar.

## ACKNOWLEDGEMENTS

Firstly, I would like to thank my family for all their support and encouragement in helping me to achieve my goal for a higher degree. Thank you for keeping the TV volume down, turning a blind eye to the box of antennas I have kept in the hall since Day 1, and a deaf ear to the constant tapping of my keyboard.

A sincere thanks to my supervisors, Assoc. Prof. Dr. Borhanuddin Mohd. Ali, Prof. M.R. Mukerjee and Pn. Ratna Kalos Zakiah Sahbudin for their guidance and constructive ideas that helped speed up the progress of my work. Thank you for always making time to meet with me and understanding my hectic schedule.

Special thanks to Mohamed Hadi Habaebi for his helpful ideas and for always taking time to help me with my work.

I would also like to thank my friends and colleagues at Telekom R&D namely Mr. Ong Che Ho, Mr. Rajan and Mr. Sivam from the PCB Lab for helping me with my layout and fabrication. Thanks to Sapura Research Sdn. Bhd. for allowing me to use their equipment without hassle, and special thanks to En. Ali Mustafa for helping me tweak my pre-amplifier.

I certify that an Examination Committee met on 8 March, 2000 to conduct the final examination of Sharlene Thiagarajah on her Master of Science thesis entitled "Active Microstrip Antenna Design for Global Positioning System Application" in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

**RAHMAN WAGIRAN, M.S.**

Department of Electrical and Electronic Engineering  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**BORHANUDDIN MOHD. ALI, Ph.D.**

Associate Professor/Head  
Department of Computer and Communication System Engineering  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**M. R. MUKERJEE, Ph.D.**

Professor  
Department of Computer and Communication System Engineering  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)

**RATNA KALOS ZAKIAH SAHBUDIN, M.S.**

Department of Computer and Communication System Engineering  
Faculty of Engineering  
Universiti Putra Malaysia  
(Member)




.....  
**MOHD. GHAZALI MOHAYIDIN, Ph.D.**  
Professor/Deputy Dean of Graduate School

Date: **20 MAR 2000**



This thesis was submitted to the Senate of Universiti Putra Malaysia and was accepted as fulfilment of the requirements for the degree of Master of Science.

  
.....  
**KAMIS AWANG, Ph.D.**  
Associate Professor,  
Dean of Graduate School,  
Universiti Putra Malaysia.

Date: **11 MAY 2000**

## DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.

  
.....  
(SHARLENE THIAGARAJAH)

Date: 9 March, 2000

## TABLE OF CONTENTS

	Page
ABSTRACT .....	ii
ABSTRAK .....	iv
ACKNOWLEDGEMENTS .....	vi
APPROVAL SHEETS .....	vii
DECLARATION FORM .....	ix
LIST OF TABLES .....	xiii
LIST OF FIGURES .....	xiv
LIST OF ABBREVIATIONS .....	xvii

## CHAPTER

I	INTRODUCTION .....	1
	Global Positioning System Overview .....	2
	GPS System Architecture .....	2
	GPS Signal Characteristics .....	3
	GPS Service Accuracy .....	4
	GPS Receivers .....	5
	Antenna Performance Requirement for GPS .....	7
	Amplitude Radiation Pattern .....	7
	Phase Radiation Pattern .....	8
	Gain .....	9
	Frequency and Polarization .....	9
	Scope of Research .....	10
II	LITERATURE REVIEW .....	11
	Crossed-Drooping Dipole .....	12
	Quadrifilar Helix .....	13
	Spiral Antennas .....	16
	Printed Cylindrical Slot .....	18
	Microstrip Patch Antenna .....	20
	Performance Evaluation .....	22
	Qualitative and Subjective Analysis .....	22
	Operational Issues .....	25
	Commercial Viability .....	26
	Fabrication Sensitivity Analysis of the MSA .....	27
	Patch Dimensions .....	27
	Substrate Permittivity ( $\epsilon_r$ ) .....	28
	Substrate Thickness (h) .....	28
	Probe Feed .....	29
	Conclusion .....	29

III	MICROSTRIP ANTENNA THEORY .....	31
	Basic MSA Characteristics .....	32
	Radiation Fields .....	32
	Analysis Models .....	34
	Microstrip Laminate Parameters .....	35
	Substrate Permittivity ( $\epsilon_r$ ) .....	35
	Substrate Thickness (h) .....	36
	Groundplane Characteristics .....	37
	Surface Roughness .....	38
	Microstrip Performance Parameters .....	38
	Magnetic Current Distribution .....	38
	Radiation Pattern .....	40
	Quality Factor and Bandwidth .....	41
	Radiation Efficiency .....	41
	Directivity and Gain .....	42
	Input Impedance .....	43
	Scattering Parameters .....	43
	Circular Polarization .....	44
	Dual Feed Configuration .....	45
	Single Feed Configuration .....	46
	Conclusion .....	47
IV	PROPOSED ACTIVE PATCH ANTENNA WITH AND WITHOUT PARASITIC .....	48
	Circular Polarized Microstrip Antenna .....	49
	Circular Patch Design .....	49
	Square Patch Design .....	52
	Pre-amplifier Design .....	53
	Schematic Diagram .....	53
	Component Selection .....	54
	Printed Circuit Board Layout .....	56
	Limited Groundplane and Parasitic Configuration .....	58
	Limited Groundplane Configuration .....	58
	Parasitic Configuration .....	59
	Measurement Procedures .....	60
	Site Acquisition .....	60
	Equipment Configuration .....	61
	Conclusion .....	62

V	MEASUREMENT RESULTS AND ANALYSIS .....	64
	Microstrip Antenna Measurements .....	65
	Design and Fabrication Sensitivity to Geometry .....	66
	Effect of Radiating Patch Size .....	67
	Active Patch Antenna .....	69
	Pre-amplifier Measurements .....	69
	Integrated Patch Measurements .....	69
	Limited Groundplane and Parasitic .....	71
	Limited Groundplane Effects .....	71
	Parasitic Effects .....	74
	Proposed Applications .....	76
	Active Limited Groundplane Antenna .....	77
	Satellite Acquisition Measurements .....	79
	Proposed Active Patch .....	80
	New Limited Groundplane Active Patch .....	82
	Conclusion .....	83
VI	CONCLUSIONS .....	85
	BIBLIOGRAPHY .....	89
	BIODATA OF AUTHOR .....	92

## LIST OF TABLES

		Page
Table 1	Performance Comparison of the Crossed-Drooping Dipole, Conventional and Printed Quadrifilar Helix, Archimedean Spiral, Conical Spiral, Printed Cylindrical Slot and Microstrip Patch Antenna Design .....	23
Table 2	Typical Values Obtained from Rogers Microwave Products .....	36
Table 3	The First Five Non-Zero Roots of $J_n(X) = 0$ .....	50
Table 4	Optimized Dimensions for a RHCP Circular Patch with Laminates RT6002 and TMM6 .....	51
Table 5	Optimized Dimensions for a RHCP Square Patch with Laminates RT6002 and TMM6 .....	53
Table 6	PCB Transmission Line Characteristics .....	57
Table 7	Experimental Results for Circular and Square Patch Antennas .....	65
Table 8	Pre-Amplifier Measured Results .....	69
Table 9	Measured Results of Square TMM6 Patch at L1 .....	72
Table 10	Measured Results of Square TMM6 Patch With and Without Parasitic .....	75
Table 11	Satellite Acquisition Data .....	80

## LIST OF FIGURES

		<b>Page</b>
Figure 1	Inverted V-Type Crossed Drooping Dipole .....	12
Figure 2	Physical Configuration of a Conventional $\frac{1}{2}$ -turn $\lambda/2$ QHA .....	14
Figure 3	Printed $\frac{1}{2}$ -turn $\lambda/2$ QHA with Infinite Microstrip Feeding Baluns .....	16
Figure 4	Geometry of a Typical Conical Spiral Antenna .....	17
Figure 5	Physical Configuration of a Conventional Slotted Cylindrical Antenna .....	18
Figure 6	Printed Cylindrical Slot using Microstrip Baluns .....	19
Figure 7	Typical Rectangular Patch Antenna Configuration .....	20
Figure 8	Microstrip Antenna Configuration .....	32
Figure 9	Side View of a Rectangular Patch .....	33
Figure 10	Radiation of a Rectangular Patch (Top View) .....	34
Figure 11	(a) Electrical Field and Magnetic Surface Current Distributions on Side Walls For $TM_{10}$ , $TM_{01}$ and $TM_{20}$ Mode. (b) Magnetic Surface Current Distribution of the $nm$ th Mode for Circular Patch .....	39
Figure 12	Flow Graph of a Two-Port Network .....	44
Figure 13	Typical Arrangement of a Dual Feed Circularly Polarized Microstrip Antenna (a) Hybrid Method (b) Offset Method .....	45
Figure 14	Typical Configuration of a Single Feed Circularly Polarized Microstrip Antenna for Various Geometry .....	46
Figure 15	RHCP Circular Patch Design .....	51
Figure 16	RHCP Square Patch Design .....	52

Figure 17	Pre-amplifier Schematic .....	54
Figure 18	Configuration of a Limited Groundplane Patch Antenna ..	59
Figure 19	Configuration of a Square Patch with Parasitic .....	59
Figure 20	Graphical Representation of a Rough Terrain .....	61
Figure 21	Graphical Representation of Far-Field Distance .....	61
Figure 22	Measurement Configuration and Equipment Set Up .....	62
Figure 23	Measured VSWR Plots for RT6002 Circular and Square Patches .....	66
Figure 24	Measured VSWR Plots for TMM6 Circular and Square Patches .....	67
Figure 25	Radiation Pattern of Circular and Square Patch Antennas	68
Figure 26	Return Loss Plot of an Active and Passive MSA .....	70
Figure 27	VSWR Plot of an Active and Passive MSA .....	71
Figure 28	Radiation Pattern of Square TMM6 Patch with Limited Groundplane .....	73
Figure 29	VSWR Plot of Square TMM6 Patch for Different Groundplane Size .....	73
Figure 30	Effect of Limited Groundplane for Different Patch Geometry and Size .....	74
Figure 31	Radiation Pattern of Square TMM6 Patch with Limited Groundplane and Parasitic .....	75
Figure 32	Effect of Parasitic Height on Radiation Pattern (Square Patch -RT6002) .....	76
Figure 33	VSWR Response of Passive and Active Limited Groundplane Antenna .....	78
Figure 34	Return Loss Plot of Passive and Active Limited Groundplane Antenna .....	78



Figure 35	Graphical Representation of Satellite Positions .....	81
Figure 36	Satellite Positions using Active Limited Groundplane MSA .....	82

## LIST OF ABBREVIATIONS

2D	2-Dimensional
AMPS	Advanced Mobile Phone System
AUT	Antenna Under Test
BW	Bandwidth
C/A Code	Coarse Acquisition Code
DGPS	Differential GPS
GIS	Geographical Information Systems
GPS	Global Positioning System
HPBW	Half-Power Beamwidth
LHCP	Left-Hand Circular Polarization
LNA	Low Noise Amplifiers
MCS	Master Control Station
MMIC	Monolithic Microwave Integrated Circuits
MNM	Multiport Network Modeling
MSA	Microstrip Antenna
MTTF	Mean Time To Failure
P Code	Precision Code
PCB	Printed Circuit Board
PPS	Precise Positioning Service
PRN	Pseudo-Random Noise
QHA	Quadrifilar Helix Antenna
$Q_0$	Unloaded Quality Factor

RF	Radio Frequency
RHCP	Right-Hand Circular Polarization
RSSI	Received Signal Strength Indicator
SMM	Spiral-Mode Antenna
SPS	Standard Positioning Service
SS	Signal Strength
$\tan\delta$	Tangent loss
TEM	Transverse Electromagnetic
TM	Transverse Magnetic
UTC	Universal Time Clock
VSWR	Voltage Standing Wave Ratio
WLL	Wireless Local Loop
$\alpha$	Groundplane Size
$\beta$	Parasitic Height
$\epsilon_r$	Substrate Permittivity
$\sigma$	Conductivity
$\lambda$	Wavelength

# **CHAPTER I**

## **INTRODUCTION**

Global Positioning System (GPS) is a worldwide satellite-based radio-navigation system developed in the 1970's for the military but has since been adopted for various commercial applications. The United States Government still maintains the highest level of positioning accuracy for the military, but a special Civilian Access code which provides lower positioning accuracy have been developed and made available to everyone.

Navigation receivers are made for aircraft, ships, ground vehicles and even hand-portables for individuals. With the advent of electronic miniaturization, bulky GPS receivers have given way to smaller, lighter and cheaper sets thus driving the need for smaller antenna designs to improve aesthetic appearance (Fisher and Ghassemi, 1999, Enge and Misra, 1999).

This thesis investigates the microstrip antenna and other low planar radiators for a commercial land-based GPS application. The proposed antenna system should be robust enough to be mounted via a magnetic base on the roof of a vehicle and provide sufficient coverage to enable it to be used with a single channel GPS receiver.

## **Global Positioning System Overview**

GPS can be used worldwide for navigation, positioning and time dissemination functions. Positioning can be determined by calculating the distances from at least three satellites and then using simple triangulation to calculate the receiver's current 2-Dimensional (2D) positioning, i.e. latitude and longitude. If a fourth satellite is available, then even altitude information can be provided (3D).

Positioning information is used for vehicle tracking and is popular for managing large vehicle deployments, for security and anti-theft purposes. GPS also provides accurate clocks that can be used to synchronize all clock equipment, especially useful in a Telecommunications Exchange for accurate billing records. GPS is also used for surveying, mapping and the gathering of information for Geographical Information Systems (GIS) and remote sensing applications.

### **GPS System Architecture**

The GPS system architecture consists of a Space Segment, Control Segment and User Segment. The Space Segment is an earth-orbiting constellation of 24 NavStar satellites (21 plus 3 on-orbit operational spares) in six orbital planes. The spacing of satellites in their orbital planes are arranged such that a minimum of four satellites will be in view anywhere on and near the surface of the earth at any one time. These satellites operate in circular 20,200km (10,900 nautical miles) orbits at an inclination angle of 55° and with a 12-hour period (Dana, 1998).

The Control Segment consists of 1 Master Control Station (MCS), 5 Monitor Stations and 3 Ground Antennas. The Monitor Stations passively track all satellites

in view, performing almost no processing of data. They send their raw pseudo-range measurements and a 50Hz (navigation) observation message back to the MCS for processing in real time. The MCS then determines each satellite's orbit and updates each satellite's navigational message. Updated information is transmitted to each satellite via the Ground Antennas.

The Ground Antennas are unmanned installations, remotely controlled by the MCS. They provide the Control-Space interface which enable the MCS to command and control the on-orbit NavStar satellites.

The GPS User Segment consists of the GPS receiver and its antenna. GPS receivers convert received signals into position, velocity and time estimates. There are many types of user equipment with different levels of accuracy, customized for various applications.

### **GPS Signal Characteristics**

The satellite works by transmitting two L-band frequencies,  $L1 = 1575.42$  MHz and  $L2 = 1227.6$  MHz, where frequency L1 is made available to everyone. Signal L2 is available in two coded variations, one of which is scrambled for military use. The most precise information is contained in the carrier wave L1 that cannot be scrambled. The three pseudo-random noise (PRN) codes are as follows,

- The Coarse/Acquisition (C/A) code has a 1.023 MHz chip rate, a period of 1 ms and is used primarily to acquire the Precision (P) Code.
- The Precision (P) code has a 10.23 MHz rate, a period of 7 days and is the principal navigation ranging code.

- The Y-code is used instead of the P-code whenever the anti-spoofing (Selective Availability) mode of operation is activated.

The C/A code is available on the L1 while the P-code is available on both L1 and L2. Thus L1 is modulated with two signals in phase quadrature, the C/A code and the P-code, while L2 is modulated only with the P-code. All 24 orbiting satellites transmit on the same frequencies, L1 and L2, where each satellite has a unique C/A and P-code.

The C/A code modulates the L1 carrier signal, 'spreading' it over a 1 MHz bandwidth, hence providing a large margin of resistance to interference. Superimposed on these PRN codes are the navigational data that a GPS receiver uses to calculate its position. The data sent are at a much lower rate than the PRN code.

### **GPS Service Accuracy**

GPS provides two levels of service, Standard Positioning Service (SPS) and the Precise Positioning Service (PPS). The low accuracy of the SPS service can be further improved using a Differential Receiver. SPS is provided on the GPS frequency L1, which contains a course acquisition (C/A) code and a navigation data message. The accuracy of this service is degraded intentionally by manipulating navigation messages, orbit data (epsilon) and/or satellite clock frequency (dither).

This random effect is called Selective Availability, and it affects all civilian GPS receivers the same way. According to the USA Federal Radio-Navigation Plan (1990), SPS provides a 95% accuracy which translates into a predictable positioning

PERPUSTAKAAN  
UNIVERSITI PUTRA MALAYSIA

accuracy of 100m horizontally, 156m vertically and a time transfer accuracy to the Universal Time Clock (UTC) within 340ns.

PPS is available on a worldwide basis to authorized users only. This service will be denied to unauthorized users by the use of cryptography. Differential GPS (DGPS) has been developed to improve GPS accuracy by adding a land-based reference receiver at an accurately surveyed site. This non-moving DGPS reference station can determine where each satellite is located in space at any given moment as well as its own location, hence the station can compute theoretical distances and the signal travel times between itself and each satellite. These theoretical measurements are compared to actual satellite transmissions and the difference represents the 'error' in the satellite's signal due to the selective availability phenomenon. This data is then used to correct the GPS receiver's own measurements. Naturally, a separate receiver is required to receive DGPS signals and the GPS receiver must be able to process DGPS data. Currently, there are two sources of corrective DGPS signals:

- Coast Guard, land-based beacon transmitters, broadcasting the data at no charge to the public, but limited primarily to coastal areas.
- FM radio sub-carriers transmissions, available in both coastal and inland areas, but limited to paid subscribers.

### **GPS Receivers**

There are two main categories of GPS receivers, the Multiplexing Receivers and the Parallel Channel Receivers. They refer to how a receiver gets and processes



information from the satellites, bearing in mind that the receiver must first capture and then measure the signals of at least three different satellites in order to navigate.

### **Multiplexing Receivers**

Multiplexing receivers use a short cut to achieve triangulation. They establish contact with a satellite only long enough to sample its data, then hunt for another satellite to sample and acquire data, then a third and possibly a fourth. This process takes at least several seconds. In order to provide a one second update, most multiplexing receivers grab an update from a couple of satellites and make a 'best guess' at the position update.

Multiplexing receivers are the least expensive types of receivers, but provide less accurate positioning responses to changes in direction and speed. With only one channel to receive, the information has to be pieced together and then averaged. Because of all this switching, multiplexing receivers tend to have more problems finding and keeping contact with satellites in areas covered by foliage or where parts of the sky are blocked by mountains, hills, trees, cliffs, slopes or even tall buildings.

### **Parallel Channel Receivers**

Parallel Channel Receivers maintain a constant simultaneous lock on several satellites at once, eliminating the switching inaccuracies of multiplexing receivers. Some GPS units use at least five parallel channel receivers. This means that there are five dedicated channels reserved for satellite communications. Three channels lock on to satellites to triangulate a longitude/latitude position while the fourth channel